

MAX. VOC 150 g/L

This product meets SCAQMD Rule  
1113-Architectural Coatings;  
Metallic Pigmented Coatings

Modern Masters Inc.  
Valencia, CA 91355 USA  
(800) 942-3166

[modernmasters.com](http://modernmasters.com)

© 2016, Modern Masters Inc.  
Made in USA

CONFORMS TO ASTM D4236

ME20816



MM200091 0316

**Metal Effects® Oxidizing Iron Paint** contains real iron particles that will oxidize when **Metal Effects Rust Activator** is applied over the **Oxidizing Iron Paint**. This combination creates a beautiful, real, rusted metal finish. **SURFACE PREPARATION:** Apply two coats of **Metal Effects Primer** per the instructions on the label and allow to cure. **APPLICATION:** Apply two coats of **Oxidizing Iron Paint** with a brush, roller or spray gun with compressor and let dry. Apply **Rust Activator** with a brush, sea sponge or spray by attaching the **Spritzer Cap**. After 5 minutes reapply **Rust Activator**. **PROTECTION:** If finish will be handled or there is a concern about staining surrounding areas, seal and protect using **Metal Effects Permacoat Xtreme** per instructions.

**WARRANTY:** This product will perform as claimed if directions are followed. Directions are as complete as possible, but cannot encompass all conditions, applications, techniques and/or surfaces, which are beyond our control. Warranty is limited to replacement or refund value of product actually used if such product proves defective within two years of manufacture. No other warranty is expressed or implied.



# METAL EFFECTS®

## OXIDIZING IRON PAINT

Water Base    16 fl. oz. / 473 ml    Low VOC

**COVERAGE:** Covers approx. 37 sq. ft./16 fl. oz., 3.4m<sup>2</sup>/473ml.

**DRY TIME:** Recoat time is approx. 1/2 hour. Dry time is approx. 1 hour. The dry time will vary with temperature and humidity.

**CLEAN UP:** Clean brushes, rollers, tools and equipment with warm, soapy water immediately after use.

**HANDLING & STORAGE:** Close container after each use. Protect from freezing. If contents freeze, allow to thaw at room temperature before use. **Stir thoroughly before use.** Do not apply at temperatures below 55°F/13°C. Dispose of unused or unwanted product in accordance with local laws regulating water base coatings.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**HEALTH & SAFETY:** Avoid contact with eyes. Wash hands after use. Do not take internally. When spraying or sanding wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for use.

**KEEP OUT OF REACH OF CHILDREN**